



an EnerSys® company

Cordex® 1.1kW

Modular Switched Mode Rectifier

Distributed in Australia by:

Alpha
Power Systems



- Switch mode rectifier provides 8.8A output @ 125VDC or 5A @ 220VDC
- Power limiting and wide range AC input
- 93% peak efficiency with power factor correction
- Convection cooled
- Hot swappable, 4RU ultra compact design

Cordex® rectifiers bring advanced technology to the DC power industry. Innovative engineering combines the best in efficiency and reliability meeting the power requirements for a variety of system applications.

This rectifier is specifically designed to recharge all types of stationary batteries for large utility, petrochemical and industrial uses.

The Cordex® 1.1kW is a compact 4RU allowing six rectifiers per 19" shelf. In addition to a range of standard features, the convection cooling will maintain ideal operating temperatures in the often dusty environments of utility applications.

Local and remote setup, adjustment and control is a simple, single-step process with the Cordex® CXC System Controller. By utilizing TCP/IP technology, complete configuration and monitoring of power equipment is possible through a network web browser.

Cordex® 1.1kW Modular Switched Mode Rectifier

125V P/N: 010-579-20-041

220V P/N: 010-569-20-041

Electrical	
Input Voltage:	Nominal: 208 to 240VAC Operating: 85 to 320VAC Extended: 150 to 176VAC (de-rated to 75%)
Input Frequency:	45 to 70Hz
Power Output:	1100W continuous/module
Power Factor:	>0.99 (input current)
THD:	<5%
Efficiency:	>93% peak nominal conditions
Output Voltage:	125V: 90 to 160VDC 220V: 180 to 320VDC
Output Current:	125V: 8.8A @ 125VDC (11A max) 220V: 5A @ 220VDC (5.5A max)
Load Regulation:	Static <±0.7%
Line Regulation:	Static <±0.1%
Transient Response:	<±2% for 40 to 90% load step, 20ms recovery time
Wide Band Noise:	<ul style="list-style-type: none"> <30mVrms <150mVp-p
Insulation:	<ul style="list-style-type: none"> 2.5kVAC input-earth 3kVAC input-output 2kVAC output-earth 0.5kVAC signals-earth
Performance / Features	
Indicators:	AC mains OK — green LED Module OK — green LED Module alarm — red LED
Cooling:	Natural convection
Adjustments (via CXC controller):	<ul style="list-style-type: none"> Floot and equalize voltage Battery test voltage High and low voltage alarms Current limit Start delay time
Protection:	<ul style="list-style-type: none"> Current limit/short circuit Input fuses Output high voltage shutdown Output power limiting Thermal foldback/shutdown Input transient AC low line foldback/shutdown AC high voltage shutdown Earth leakage alarm

Mechanical		
Dimensions:	mm: 177H x 71W x 250D inches: 6.9H x 2.8W x 9.8D	
Weight:	125V: 3.2kg (7.1lbs) 220V: 2.9kg (6.4lbs)	
Environmental		
Temperature: (Based on 3 modules installed)	125V	Operation: -40 to 42°C (-40 to 107.6°F) Extended: 65°C/149°F 600W Storage: -50 to 85°C (-58 to 185°F)
	220V	Operation: -40 to 48°C (-40 to 118.4°F) Extended: 65°C/149°F 600W Storage: -50 to 85°C (-58 to 185°F)
Humidity:	0 to 95% RH non-condensing	
Elevation:	-500 to 4000m (-1640 to 13120ft)	
Heat dissipation:	125V: <400 BTU per hour (max)/117 Watts 220V: <282 BTU per hour (max)/83 Watts	
Shelves		
P/N: 030-740-20		
19" shelf (6 module)		
Dimensions:	mm: 177H x 444W x 303D inches: 6.9H x 17.5W x 11.9D	
Weight:	7.3kg (16lbs)	
Mounting:	<ul style="list-style-type: none"> Fits 19" rack flush mount Fits 19" or 23" center mount 	
Connections:	Input: Terminal blocks for 3 feeds 4 – 6mm ² (12 – 10AWG) Output: ¼" studs on ¾" centers Chassis Ground: ¼" stud CAN Communication: RJ 12 offset	
Agency Compliance		
Cordex® 1.1kW is designed to meet the following:		
Safety:	<ul style="list-style-type: none"> CSA C22.2 No 60950-1-03 UL 60950-1 1st edition CE marked IEC/EN 60950-1 	
EMC:	ETSI 300 386 Emissions: <ul style="list-style-type: none"> CFR47 (FCC) Part 15 Class A ICES-03 Class A EN55022 (CISPR 22) Class A C-Tick (Australia) EN 61000-3-2 EN 61000-3-3 Immunity: <ul style="list-style-type: none"> EN 61000-4-2 EN 61000-4-3 EN 61000-4-4 EN 61000-4-5 EN 61000-4-6 EN 61000-4-11 ANSI/IEEE C62.41 Cat B3 	

For more information, please contact Australian Distributor:



Alpha Power Systems Pty Ltd
18/30 Heathcote Road
Moorebank NSW 2170
Australia

Phone: +61 2 96028331
Fax: +61 2 96029180
E-mail: admin@alphapower.com.au
Website: www.alphapower.com.au



an EnerSys® company

Alpha Technologies Services, Inc. USA: 3767 Alpha Way, Bellingham, WA 98226 Canada: 7700 Riverfront Gate, Burnaby, BC V5J 5M4
Toll Free North America: +1 800 322 5742 Outside US: +1 360 647 2360 Technical Support: +1 800 863 3364
For more information visit www.alpha.com

© 2020 Alpha Technologies Services, Inc. All Rights Reserved. Trademarks and logos are the property of Alpha Technologies Services, Inc. and its affiliates unless otherwise noted. Subject to revisions without prior notice. E. & O.E.

08/2020

#0480043-00 REV B