





- > 350W/VA UPS module designed to operate in extreme environments; providing maximum flexibility while ensuring critical loads remain protected and running during power outages and other power disturbances
- > Unsurpassed flexibility with dual 120Vac and 24Vac outputs
- > Wide range Automatic Voltage Regulation (AVR) lengthens battery life by providing protection without transferring to backup mode during voltage surge or sag
- > Local and remote monitoring and control via USB port and Ethernet SNMP interface
- > Temperature compensated battery charging protects batteries from overcharging at extreme temperatures, extending the life of the battery
- Independently programmable control and report dry contacts allow monitoring and controlling of key functions

Alpha FXM is a line of rugged UPS power modules used worldwide in the most demanding environments where clean backup power is needed. Designed to perform in the most extreme demanding environments, Alpha FXM units ensure equipment in security, communications, traffic, industrial environments, and many other critical applications remain safe and protected from power disturbances. Thanks to its powerful programmable battery charger, the FXM is capable of providing the runtime you need. All FXM models are available in 120Vac and 230Vac.





FXM 350 Rugged UPS Module

Consult your Alpha representative for P/N configurations

Electrical

>120Vac Model

Battery string voltage:48Vdc or 24Vdc
Nominal voltage:120Vac
Frequency:
nput:
Voltage range (w/o transferring to battery mode): 88 to 152Vac
Current:
• FXM350-24:5.3A
• FXM350-48:5.7A
Output:
Waveform:Pure sinewave
Nominal voltage:Dual 120Vac, 24Vac
Voltage regulation:±10%
Power at 50°C:350W/VA Total
• 24Vac:
• 120Vac:350W/VA (max)
Frequency:Output frequency = Input frequency
>230Vac Model

Battery string voltage:	24Vdc
Nominal voltage:	230Vac
Frequency:	60/50Hz ±5% (auto-detection)
Input:	
Voltage range (w/o trans	erring to battery mode): 151 to 282Vac
Current:	2.7A
Output:	
Waveform:	Pure sinewave
Nominal voltage:	230Vac, 24Vac
Voltage regulation:	±10%
Power at 50°C:	350W/VA Total
• 24Vac: 260VA (max)	
• 230Vac: 350VA (max)	
Frequency	Output frequency = Input frequency

Mechanical

Mounting:	. 19" or 23" rack with the addition of ears for rack mounting
Dimensions: mm: inches: Weight:	. 3.5H x 13.46W x 7.8D
Environmental	
Operating temp range: Audible noise @ 25°C:	

Performance

Typical output voltage THD:.. <3%

Power Connector Options

120Vac Model							
Input		Output					
	Terminal Block	(<u> </u>	Terminal Block				
	Terminal Block		Terminal Block				
		Terminal Block	Terminal Block				

Agency Compliance

Electrical safety:.....UL1778, CSA C22.2 No. 107.3,

EN60950-1, EN62040-1-2



EMI:FCC Part 15/B, EN55022. Class A. EN62040-2

*Derates above 50°C (122°F)

**CE applies to 230Vac version only



For more information, please contact:

Alpha Power Systems Pty Ltd 18/30 Heathcote Road Moorebank NSW 2170 Australia

Phone: +61 2 9602 8331 Fax: +61 2 9602 9180 E-mail: admin@alphapower.com.au Website: www.alphapower.com.au

Alpha Technologies Ltd.

Canada: Burnaby, British Columbia Tel: 604 436 5900 Fax: 604 436 1233 United States: Bellingham, Washington Tel: 360 647 2360 Fax: 360 671 4936

Alpha Technologies reserves the right to make changes to the products and information contained in this document without notice. Copyright © 2013 Alpha Technologies. All Rights Reserved. Alpha® is a registered trademark of Alpha Technologies. member of The Alpha Group™ is a trademark of Alpha Technologies.

For more information visit www.alpha.ca

#0480016-00 Rev H (06/2013)

member of The चीनीच Group™