



an EnerSys® company

CXC HP 6i-ADIO

CXC HP Smart Peripheral

Distributed in Australia by:

Alpha
Power Systems



- CXC HP series ADIO peripheral with flexible rack, panel, and DIN mounting options
- I/O expansion via CAN bus for advanced site monitoring applications, including support for future growth
- Provides six accurate monitoring channels for current measurements

The Cordex® CXC HP 6i-ADIO offers modular and expandable current input monitoring to power solutions and monitoring applications using CXC HP series controllers.

The 6i-ADIO is part of the CXC HP series of advanced I/O peripherals incorporating flexible mounting, high accuracy and many advanced features via the HP control platform.

The 6i-ADIO provides 6 current inputs and is seamlessly recognized by the CXC HP control platform which also provides advanced setup wizards to create various power systems using Cordex power conversion products such as rectifiers, converters, inverters and line powering solutions.

The 6i-ADIO and other IO peripherals ensure effortless operation and management capability to satisfy the most demanding and advanced energy system applications.

CXC HP 6i-ADIO Smart Peripheral

P/N: 0180051

Electrical	
Input Voltage:	10 to 60Vdc
Features	
Local Alarms:	Power ON (Blue) Communications OK (Green)
Communication Ports:	CAN In/Out (RJ12 Offset)
Controller I/O:	
Current Shunt Inputs:	6 (25 to 200mV)
Mechanical	
Mounting:	CXC HP 3U rack panel mount (0180046) or DIN/Panel mounting (0370196)
Dimensions:	mm: 131.3H x 83.9W x 28.9D inches: 5.1H x 3.3W x 1.2D
Weight:	0.20kg (0.44lbs)

Environmental	
Temperature:	
Extended:	-40 to 65°C (-40 to 149°F)
Humidity:	0 to 95% RH non-condensing
Elevation:	-500 to +4000m (-1640 to 13124ft)
Agency Compliance	
Safety:	CSA C22.2 No 60950-1-03 CE marked
EMC:	ETSI 300 386
Emissions:	CFR47 (FCC) Part 15 Class B ICES-03 Class B EN55022 (CISPR 22) Class B
Immunity:	EN 61000-4-2 EN 61000-4-3 EN 61000-4-4 EN 61000-4-5 EN 61000-4-6
NEBS:	NEBS L3 Certified

For more information, please contact Australian Distributor:



Alpha Power Systems Pty Ltd
18/30 Heathcote Road
Moorebank NSW 2170
Australia

Phone: +61 2 96028331
Fax: +61 2 96029180
E-mail: admin@alphapower.com.au
Website: www.alphapower.com.au



Alpha Technologies Services, Inc. USA: 3767 Alpha Way, Bellingham, WA 98226 Canada: 7700 Riverfront Gate, Burnaby, BC V5J 5M4
Toll Free North America: +1 800 322 5742 Outside US: +1 360 647 2360 Technical Support: +1 800 863 3364
For more information visit www.alpha.com

an EnerSys® company

© 2020 Alpha Technologies Services, Inc. All Rights Reserved. Trademarks and logos are the property of Alpha Technologies Services, Inc. and its affiliates unless otherwise noted. Subject to revisions without prior notice. E. & O.E.

06/2020
#0470318-00 REV A