



an EnerSys® company

CXC HP HV-ADIO

CXC HP Smart Peripheral

Distributed in Australia by:

Alpha
Power Systems



- CXC HP series ADIO peripheral with flexible rack, panel, and DIN mounting options
- Enables High Voltage (125/220Vdc) system support using the advanced CXC HP Control platform
- I/O expansion via CAN bus for advanced site monitoring applications, including support for future growth
- Integrated Ground Fault Detection (GFD) to alarm system fault conditions
- On board DC-DC converter permits use with standard CXC HP low voltage controllers

The Cordex® CXC HP HV-ADIO brings advanced control and monitoring to Alpha Cordex 125/220Vdc rectifiers and systems.

The HV-ADIO is part of the CXC HP series of advanced I/O peripheral incorporating flexible mounting, high accuracy, and the advanced features in the HP control platform.

The HV-ADIO provides a variety of analog inputs, digital inputs and high voltage rated relay outputs. The ADIO device is seamlessly recognized by the CXC HP control platform which also provides advanced setup wizards to create high voltage DC systems using Cordex rectifiers.

An integrated Ground Fault Detection (GFD) circuit is also provided to enable visibility to earth leakage currents. This feature can be easily disabled for operators who wish to use 3rd party GFD devices.

Cordex CXC HP controllers and ADIO peripherals ensure effortless operation and management capability to satisfy the most demanding and advanced energy system applications.

CXC HP HV-ADIO Smart Peripheral

P/N: 0180057

Electrical	
Input Voltage:	90 to 300Vdc
Input Power:	50W (125Vdc 0.4A; 220Vdc 0.2A)
Output Power:	30Vdc; Max 1A, 30W (For feeding low voltage CXC HP controller)
DCCT Power:	±15Vdc
Features	
Local Alarms:	Power ON (Blue) Communications OK (Green)
Communication Ports:	CAN In/Out (RJ12 Offset)
Ground Fault Detection:	1 user configurable (Adjustable up to 15mA) on V2 input channel
Controller I/O:	
Voltage Inputs:	2 (±300Vdc)
Current Shunt Inputs:	1 (25 to 200mV)
DCCT Current Inputs:	2 (±10Vdc signal)
Temperature Inputs:	2
Digital Inputs:	4 (Contact closure detect – 5Vdc Max)
Relay Outputs:	6 (Form C, 220Vdc 50W max)
Mechanical	
Mounting:	CXC HP 3U rack panel mount (0180046) or DIN/Panel mounting
Dimensions:	mm: 198H x 84W x 38D inches: 7.8H x 3.3W x 1.5D
Weight:	1kg (2lbs)

Environmental	
Temperature:	
Extended:	-40 to 65°C (-40 to 149°F)
Humidity:	0 to 95% RH non-condensing
Elevation:	-500 to +4000m (-1640 to 13124ft)
Agency Compliance	
Safety:	CAN/CSA-C22.2 No 60950-1-07+Am1+Am2 ANSI/UL 60950-1-2014 IEC 60950-1:2005 (Second Edition) + Am 1:2009 + Am 2:2013 CE marked
EMC:	EN 61000-6-3 EN 55032 EN 61000-6-2
Emissions:	FCC CFR 47, Part 15 Subpart B Class B ICES-003 Class B EN 55022 Class B
Immunity:	EN 61000-4-2 EN 61000-4-3 EN 61000-4-4 EN 61000-4-5 EN 61000-4-6

For more information, please contact Australian Distributor:



Alpha Power Systems Pty Ltd
18/30 Heathcote Road
Moorebank NSW 2170
Australia

Phone: +61 2 96028331
Fax: +61 2 96029180
E-mail: admin@alphapower.com.au
Website: www.alphapower.com.au



Alpha Technologies Services, Inc. USA: 3767 Alpha Way, Bellingham, WA 98226 Canada: 7700 Riverfront Gate, Burnaby, BC V5J 5M4
Toll Free North America: +1 800 322 5742 Outside US: +1 360 647 2360 Technical Support: +1 800 863 3364
For more information visit www.alpha.com

an EnerSys® company

© 2020 Alpha Technologies Services, Inc. All Rights Reserved. Trademarks and logos are the property of Alpha Technologies Services, Inc. and its affiliates unless otherwise noted. Subject to revisions without prior notice. E. & O.E.

06/2020
#0470265-00 REV C