



an EnerSys® company

# Cordex® 650W

## 48VDC Modular Rectifier Shelf Systems

Distributed in Australia by:

**Alpha**  
Power Systems



- Single shelf modular rectifier solution provides multiple 48V configurations up to 67A for various 48VDC applications
- Convection cooled design for high reliability in harsh industrial environments
- Front access options for space restricted enclosures
- Integrated DC system capability with controller and distribution module options

### **Alpha's Cordex® series includes a complete range of modular 650W rectifier shelf systems to meet the needs of worldwide telecommunications applications.**

Cordex® 650W modular shelf systems are available to fit various 48VDC application needs. 19" rear access solutions are available in a five-module (3.2kW) bulk output version as well as a four-module (2.6kW) integrated solution with an AM plug-in breaker distribution module. Complete front access versions are also available in 23" (4-module) and 19" (3-module) which include a distribution module accommodating both plug-in breakers and GMT fuses. CXCI HP integrated controllers are standard with all 650W shelf systems.

The Cordex® 650W rectifier modules feature complete hot-swappability, high efficiency with power factor correction, unique power limiting capability and wide range input. Convection cooling and an ultra compact design also make Cordex® shelf systems ideal for the telecommunications industry.

# Cordex® 650W 48VDC Modular Rectifier Shelf Systems

## Cordex 48-650W Rectifier Shelves

### 19/23in 2RU Universal Mount



#### Cordex® 2.6kW Shelf Power System

P/N: 030-728-20-XXX

Rectifiers: 4 x CXRC 48-650W

Controller: 1 x CXCI HP

Distribution: 19/23in 2RU Universal Mount



#### Cordex® 3.2kW Bulk Power System

P/N: 030-782-20-XXX

Rectifiers: 5 x CXRC 48-650W

Controller: Optional 1x CXCI HP

Distribution: Bulk power for external distribution (optional LVD)

### Electrical

<b>Operating:</b>	140-276VAC
<b>Extended High:</b>	276-310VAC (derated input power factor)
<b>Extended Low:</b>	80-140VAC (derate linearly to 60% output power, 500W @ 120VAC)
<b>Power Output:</b>	650W at 208-240VAC Nominal 500W at 120VAC Nominal
<b>Input Current:</b>	3.0 to 3.5A (208-240VAC) 5.7A Max @ 110VAC
<b>Output Current:</b>	13.5A @ 48VDC 12A @ 54VDC

### Mechanical

<b>4 Rectifier Shelf:</b>	
<b>Dimensions:</b>	<b>mm:</b> 88H x 444W x 307D <b>inches:</b> 3.5H x 17.5W x 12.1D
<b>Weight:</b>	8.5kg (18.7lbs)
<b>5 Rectifier Shelf:</b>	
<b>Dimensions:</b>	<b>mm:</b> 88H x 444W x 303D <b>inches:</b> 3.5H x 17.5W x 12D
<b>Weight:</b>	7.3kg (16lbs)
<b>Module:</b>	
<b>Dimensions:</b>	<b>mm:</b> 88H x 71.6W x 242D <b>inches:</b> 3.5H x 2.82W x 9.53D
<b>Weight:</b>	1.6kg (3.6lbs)
Note: Dimensions do not include mounting bracket	
<b>Communication Ports</b>	
<b>CAN:</b>	Interface to control rectifiers and smart peripherals
<b>Ethernet:</b>	10/100 Base-T for TCP/SNMP features
<b>USB:</b>	Local backup and configuration transfer
<b>I/O:</b>	<ul style="list-style-type: none"> <li>• 2 Digital Inputs (one used internally on systems with distribution)</li> <li>• 1 Voltage Sensor Input</li> <li>• 2 Temperature Sensor Inputs</li> <li>• 4 Dry Contact Outputs (one used internally on systems with LVD)</li> </ul>
<b>Environmental</b>	
<b>Temperature:</b>	<b>Standard:</b> -40 to 50°C (-40 to 122°F) <b>Storage:</b> -40 to 85°C (-40 to 185°F)
<b>Humidity:</b>	0 to 95% Relative Humidity (non condensing)
<b>Elevation:</b>	-500 to 3000m (-1640 to 9840ft)
<b>Cooling:</b>	Natural convection (vertical airflow)
<b>Related Components</b>	
<b>Rectifier:</b>	010-570-20-041
<b>Rectifier Blank:</b>	613-465-W3
<b>Controller:</b>	0180056-001
<b>6ft 1/4" Lug Temp Sensor:</b>	747-028-20-071
<b>6ft 3/8" Lug Temp Sensor:</b>	747-082-20-071

For more information, please contact Australian Distributor:



Alpha Power Systems Pty Ltd  
18/30 Heathcote Road  
Moorebank NSW 2170  
Australia

Phone: +61 2 96028331  
Fax: +61 2 96029180  
E-mail: [admin@alphapower.com.au](mailto:admin@alphapower.com.au)  
Website: [www.alphapower.com.au](http://www.alphapower.com.au)



Alpha Technologies Services, Inc. USA: 3767 Alpha Way, Bellingham, WA 98226 Canada: 7700 Riverfront Gate, Burnaby, BC V5J 5M4  
Toll Free North America: +1 800 322 5742 Outside US: +1 360 647 2360 Technical Support: +1 800 863 3364  
For more information visit [www.alpha.com](http://www.alpha.com)

© 2020 Alpha Technologies Services, Inc. All Rights Reserved. Trademarks and logos are the property of Alpha Technologies Services, Inc. and its affiliates unless otherwise noted. Subject to revisions without prior notice. E. & O.E.