



an EnerSys company

Cordex[®] HP 3.0kW

Modular Switched Mode Rectifier

Distributed in Australia by:

Alpha
Power Systems



- High performance compact 62.5A rectifier for 48V telecom applications
- High efficiency, approaching 96.9% for reduced OPEX and carbon footprint
- Extended operating temperature range up to 75°C for deployment in the harshest outdoor environments
- Multiple configurations delivering up to 15kW in a compact 23" 1RU shelf
- High power density (35W/in³) yields more space for revenue generating equipment
- Wide AC input operating range for global installation requirements

Cordex High-Performance (HP) rectifiers make a proven, reliable platform even better, with significant advancements in efficiency and performance.

In a compact, fan-cooled design, HP rectifiers open the possibility to wider ranges of applications and immediate OPEX/CAPEX savings, reducing total cost of ownership and impact on the environment.

The Cordex HP 3.0kW is a perfect solution for various small to large 48Vdc capacity applications including DAS, central office, headend, backhaul and wireless base stations. It is particularly suitable for high density telecom applications and able to deliver 312A or 15kW per compact 1RU shelf.



Unlike other rectifiers in its category, the Cordex HP 3.0kW provides 100% nominal power up to 55°C ambient and at least 2400W up to 65°C. With a high operating efficiency, high power density and broad temperature operation, HP series rectifiers are also ideal for harsh outside plant enclosure installations.

Local and remote setup, adjustment and control are a simple, single-step process with the Cordex CXC HP system controller. Complete configuration and monitoring of power equipment is possible through a network web browser or via a local display.

Cordex® HP 3.0kW 48V Modular Switched Mode Rectifier

P/N: 0100037-001

Electrical	
Input Voltage:	Nominal: 208 to 277Vac Operating: 90 to 305Vac Extended: 90 to 187Vac (de-rated power)
Input Frequency:	45 to 66Hz
Power:	3000W continuous (1700W output @ 120Vac Input)
Power Factor:	>0.98 (50 to 100% load)
THD:	<8% (50 to 100% load)
Efficiency:	96.9% Peak
Output Voltage:	42 to 58Vdc
Output Current:	55A @ 54Vdc (62.5A max.@ 48Vdc) (~36AA @ 48Vdc at 120Vac Input)
Load Regulation:	<±0.5% (static)
Line Regulation:	<±0.1% (static)
Transient Response:	±3% for 40 to 90% load step
Noise:	Voice Band: <53dBmC Wide Band: <260mV RMS (10kHz to 10MHz) <180mV pk to pk (10kHz to 100MHz)
Psophometric Noise:	<2mV RMS
Acoustic:	<60dBa @ 1m (3ft), 30°C
Mechanical	
Dimensions:	mm: 41H x 104W x 33D inches: 1.6H x 4.1W x 1.3D
Weight:	1.83kg (4.04lbs)
Environmental	
Temperature:	Operating: -40 to 75°C (-40 to 176°F); full rated output up to 55°C (131°F); >2400W @ 65°C (149°F) Storage: -40 to 85°C (-40 to 185°F)
Humidity:	0 to 95% RH non-condensing
Elevation:	60 to 3000m (197 to 9842ft)
Heat Dissipation:	<585 BTU per hour (worst case)/171 Watts
Agency Compliance	
Safety:	<ul style="list-style-type: none"> CSA/UL/IEC/EN 60950-1 CE Marked
EMC:	ETSI 300 386 Emissions: <ul style="list-style-type: none"> CFR47 (FCC) Part 15 Class A EN 61000-3-2, 3-3 Immunity: <ul style="list-style-type: none"> EN 61000-4-2, 4-3, 4-4, 4-5, 4-6, 4-11 ANSI/IEEE C62.41 CatB3
NEBS / Telcordia:	<ul style="list-style-type: none"> GR-1089-CORE (pending) GR-63-CORE (pending) GR-3108-CORE (pending)

Cordex 48-3.0kW Rectifier Shelves	
23in 1RU universal mount 15000W P/N 0300216-001	
	
Rectifiers:	5 x CXRF HP 48-3.0kW
Distribution:	Bulk power for external distribution
Dimensions:	mm: 44H x 537W x 420D inches: 1.75H x 21.1W x 16.5D
Weight:	5.7kg (12.6lbs)
19in 1RU universal mount 12000W P/N: 0300228-001	
	
Rectifiers:	4 x CXRF HP 48-3.0kW
Distribution:	Bulk power for external distribution
Dimensions:	mm: 44H x 438W x 420D inches: 1.75H x 17.3W x 16.6D
Weight:	4.5kg (9.9lbs)
Communications Ports:	CAN: interface on shelf to CXC HP controller

For more information, please contact Australian Distributor:



Alpha Power Systems Pty Ltd
18/30 Heathcote Road
Moorebank NSW 2170
Australia

Phone: +61 2 96028331
Fax: +61 2 96029180
E-mail: admin@alphapower.com.au
Website: www.alphapower.com.au



an EnerSys company

Alpha Technologies Services, Inc. USA: 3767 Alpha Way, Bellingham, WA 98226 Canada: 7700 Riverfront Gate, Burnaby, BC V5J 5M4
Toll Free North America: +1 800 322 5742 Outside US: +1 360 647 2360 Technical Support: +1 800 863 3364
For more information visit www.alpha.com

© 2020 Alpha Technologies Services, Inc. All Rights Reserved. Trademarks and logos are the property of Alpha Technologies Services, Inc. and its affiliates unless otherwise noted. Subject to revisions without prior notice. E. & O.E.

06/2020
#0470352-00 REV D